




STANDARD GRAPHICS MODULES

G64240x02..... OUTLINE DIMENSION AND BLOCK DIAGRAM



The tolerance unless classified ±0.3 mm

PIN ASSIGNMENT		
Pin No.	Symbol	Function
1	FG	Frame Ground
2	VSS	Ground Terminal
3	VDD	Supply Terminal
4	V0	Power Supply for LCD Driver
5	/WR	Data Write
6	/RD	Data Read
7	/CE	Chip Enable
8	C/D	H : Instruction , L : Data
9	NC	-
10	/RESET	Reset Signal
11	DB0	Data Bus Line
12	DB1	Data Bus Line
13	DB2	Data Bus Line
14	DB3	Data Bus Line
15	DB4	Data Bus Line
16	DB5	Data Bus Line
17	DB6	Data Bus Line
18	DB7	Data Bus Line
19	FS	Font Selection
20	VOUT	Output Voltage
21	SLA	Led Backlight Power Supply
22	SLK	Led Backlight Ground

NOTE :

1. BACKLIGHT - YELLOW GREEN : BOTTOM LED BACKLIGHT
2. BACKLIGHT - OTHER COLOR : SIDE LED BACKLIGHT

ABSOLUTE MAXIMUM RATING

Item	Symbol	Conditions	Min.	Max.	Unit
Power Supply Voltage	Vdd-Vss	-	-0.3	7.0	V
Input Voltage	Vin	-	0.3	Vdd + 0.3	V
NORMAL	OPERATING TEMPERATURE	Topr	Normal	0	+50 °C
	STORAGE TEMPERATURE	Tstg	Normal	-20	+70 °C
WIDE	OPERATING TEMPERATURE	Topr	Normal	-20	+70 °C
	STORAGE TEMPERATURE	Tstg	Normal	-30	+80 °C

ELECTRICAL CHARACTERISTIC (Vdd = + 5v, Ta = 25°C)

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
Logic Supply Voltage	Vdd	-	4.5	5.0	5.5	V
"H" Input Voltage	V _{HI}	-	Vdd - 2.2	-	Vdd	V
"L" Input Voltage	V _{LI}	-	0	-	0.8	V
"H" Output Voltage	V _{OH}	-	Vdd - 0.3	-	Vdd	V
"L" Output Voltage	V _{OL}	-	0	-	0.3	V
Module Supply Current	I _{dd}	-	-	30.0	40.0	mA
LCD Driving Voltage	V _{LCD}	Vdd-Vo	12.4	13.0	13.6	V

BACKLIGHT OPTION

LED COLOR	OPTION	CONDITION	FORWARD CURRENT		
			MIN	TYP	MAX
YELLOW GREEN	YES	V _{led} = 5.0V R _{led} = 10 ohm	-	100	-
WHITE	YES	V _{led} = 5.0V R _{led} = 20 ohm	-	43	-
BLUE	NO	-	-	-	-
AMBER	NO	-	-	-	-
RED	NO	-	-	-	-
CCFL	NO	-	-	-	-
EL	NO	-	-	-	-

CCT reserves the right to vary or make changes to the specifications of the module in this brochure at any time without prior notice. CCT further assumes no responsibility for its use, nor for any infringements of patents, pending applications or the rights of thirds parties as a result of its use.