


STANDARD MODULE ORDERING INFORMATION

Note : Not all combination are available. Consult CCT or its representatives for the latest information



MODULE TYPE

C = CHARACTER
G = GRAPHIC

MODEL NUMBER

STD. CHARACTER : No. of line followed by no. of character

STD. GRAPHIC : No. of row followed by no. of column

BACKLIGHT MODE

L : Bottom Led Backlight (Yellow Green) G : Side Led Backlight (Green)
R : Bottom Led Backlight (Red) W : Side Led Backlight (White)
S : Side Led Backlight (Yellow Green) E : EL Backlight
A : Side Led Backlight (Amber) C : CCFL Backlight
B : Side Led Backlight (Blue) N : No Backlight

MODULE VERSION

Version from 01 to 99

LCD MODE

Y : Yellow Green (STN)
G : Grey (STN)
B : Black White (FSTN)
N : Negative (FSTN) Blue (Single Retardation)
U : Negative (FSTN) Black/White (Double Retardation)
S : Negative (STN)
P : Positive (HTN)

VIEWING ANGLE

T : Top view (12 O'clock)
B : Bottom view (6 O'clock)

OPERATING TEMPERATURE

N : Normal Temperature (0°C to +50°C)
W : Wide Temperature (-20°C to +70°C)

BACKLIGHT TERMINAL

FOR BACKLIGHT REVERSE CONNECTION ONLY (CHARACTER MODEL)

SEMI - CUSTOMISE (MINOR CHANGES FROM STANDARD MODEL)

00 - STANDARD MODEL

REFER TO FACTORY FOR OTHER VERSIONS. TERM AND CONDITION APPLY